

# TB 554 TRACTORS

THE MOST ROBUST TRACTORS. NO ELECTRONIC COMPONENTS

- Shibaura Engine: **A4K41T**
- Rated PTO Power: **57,7/46,8 hp/kW**
- Hydraulic pump flow: **9.3 gpm**
- Dimensions: **163" x 74" x 105"** ROPS version  
**111"** Cab version
- Weight: **5115 lbs** ROPS version  
**5567 lbs** Cab version
- Maximum speed: **40 KM/H**



The best equipped vehicles on the market  
MORE THAN \$15 000 IN FREE ADD-ONS

THE ONLY 10-YEAR or 3500 HOURS WARRANTY

- 10-year warranty - the longest warranty in the industry (value of \$3000)
- Free high-end front loader with buck with the purchase of a ROPS or Cabin Model (value of \$6600) Basic models are excluded from this promotion
- Skid-Steer loader quick attachment system (SSQA)
- First class heavy-duty agricultural hydraulic system in 3 points
- Front oil outlet - 3rd function (value of \$1500)
- 2 standard rear hydraulic outlets (value of \$2000)
- Tractor weight greater than competition, providing better traction
- Japanese-made Shibaura engine
- Diesel engine without regeneration (no DEF)
- Ceramic clutch for heavy-duty work to avoid conventional clutch slippage
- Standard agricultural radial tires (value of \$1000)
- Valve protector to limit punctures (value of \$350)
- Wheel weights in the rear tires for better traction (value of \$400)
- Sturdy front axle for heavy-duty work
- Straight rear axle with adjustable extension to meet the needs of various driveability and stabilization applications. Provides 10 inches of additional width
- 800 CCA battery for better starting in cold conditions (value of \$100)
- Sunroof (value of \$350)
- Renowned Grammer seat for ultimate comfort (value of \$500)
- Front and wear wipers (value of \$250)
- Standard AM/FM/USB/AUX radio (value of \$150)
- Sun visor to improve visibility and safety (value of \$100)
- Air conditioning (value of \$1000)
- Two replacement oil filters included to make your maintenance simpler
- Parts manual to make spare parts ordering easier
- A tool kit set for performing minor repairs and maintenance by yourself

# TB 554 TRACTORS



Engine	SHIBAURA A4K41T	
Rated Engine Power, ISO TR14396-ECE R120	55/40.4 hp/kW	
Type	4-cylinder, diesel	
Rated Engine Speed	2400 rpm	
Max. Torque, ISO TR14396	">215/1600~1800" hp/Nm	
Rated PTO Power	34.4 hp/kW	
Displacement	3.857 ltr	
Fuel Tank Capacity	60 ltr	
Transmission	Dry Dual Clutch (Ceramic disk) 10/11 in.	
12F + 12R Collar Shift/Shuttle Shift	✓	
Speed Range	8F+4R/8F+8R/12F+12R Forward 2.46-34.78 / Reverse 2.15-30.49	
	16F+8R Forward 0.37-34.78 / Reverse 0.55-12.1	
Differential Lock	✓	
Power Take-Off 540/1000 rpm	✓	
<b>BRAKE</b>		
Parking Brake	Mechanical, independent of main brakes, hand lever operated	
Drivetrain	2WD/4WD selectable	
<b>FRONT AXLE</b>		
Turning Radius without brake	4.3±0.3 m	
Turning Radius with one side brake	3.8±0.3 m	
Rear axle/lockable axle (differential lock)	✓	
Adjustable axle, rare wheel spacing	0 to 8» (203 mm)	
Hydraulic Power Lift	Force control, position control, separated force and position control	
Cat. I Three Point Hitch	✓	
Hydraulic Flow	35 l/min	
Lift Capacity at 610mm behind Hitch Point	1020 kg	
No. of Multi-way Valves	2	
Cab	ROPS	
<b>TIRES AND WEIGHTS</b>		
Front tires	Standard	8.3-20
	Optional	
Rear tires	Standard	14.9-28
	Optional	14.9-24
Structure Weight (ROPS)*	2190 kg	
Structure Weight (Cab)*	2370 kg	
Tractor Dimensions Length x Width x Height	4030 X 1650 X 2520 mm	
Wheelbase	2040	
Ground Clearance	310	

\* Tractor Dry Mass